











Pic	Part No.	Description
	BG1/LED1 BG2/LED1	Stainless Steel Gallery, LED Flashing Unit, Amber Globe Aluminium Gallery, LED Flashing Unit, Amber Globe
(Stainless Steel Gallery with Amber Globe and LED Flashing Unit Shown)		
	BG1/HFU1 BG2/HFU1	Stainless Steel Gallery, 12v 50w Halogen Flashing Unit, Hi-Glow Amber Globe Aluminium Gallery, 12v 50w Halogen Flashing Unit, Hi-Glow Amber Globe
(Aluminium Gallery with High Glow Amber Globe and Halogen Flashing Unit shown)		
	BG1/LEDR1 BG1/LEDR-LV	Non-Flashing LED, Stainless Steel Gallery, Pearl Globe (Refuge Beacon) Low Voltage LED, Non-Flashing St/St Gallery, Pearl Globe (Refuge Beacon)
	BG2/LEDR1 BG2/LEDR-LV	Non-Flashing LED, Aluminium Gallery, Pearl Globe (Refuge Beacon) Low Voltage LED, Non-Flashing, Aluminium Gallery, Pearl Globe (Refuge Beacon)
	CS-GS CS-SS	Courtesy Tube in Galvanised Mild Steel Powder Coated Black Courtesy Tube in Stainless Steel Powder Coated Black
	CP-GS CP-GS-B	Courtesy Panel Galvanised Mild Steel Powder Coated Black (Halo) Courtesy Panel Galvanised Mild Steel Powder Coated Black with White Border (Halo)
	SL4W	4 watt LED Aluminium Floodlight (for use at crossings etc ..) 50,000 hour life expectancy 300 Lumens output creating 50 Lux at 2.0m
	LED1	230v Bright White LED Flashing Unit 6 watts – 50,000 hour life expectancy
	LEDR1 LEDR-LV	230v Bright White LED Non-Flashing Unit (for Refuge Beacons) Low Voltage Bright White LED Non-Flashing Unit (for Refuge Beacons) 50,000 hour life expectancy
	HFU1	12v 50w Halogen Flashing Unit